

you can
Canon

imageFORMULA
DR-2010C / DR-2510C
Workgroup Document Scanners

Effortless Performance
from space-saving
workgroup scanners



DR-2010C / DR-2510C

imageFORMULA

Specifications DR-2010C / DR-2510C

Type Document Reading Sensor Optical Resolution Light Source Reading Side Interface Dimensions Weight Power Requirements Power Consumption Operating Environment Environmental Compliance	Desktop type sheet fed scanner CMOS CIS 1 Line Sensor 600 dpi RGB LED Front / Back / Duplex High Speed USB 2.0 Tray closed: 298 (W) x 160 (D) x 160 (H) mm Tray opened: 298 (W) x 490 (D) x 245 (H) mm Approx. 2.4kg AC100 - 240V (50/60Hz) Scanning: 16W, Sleep mode: 2.2W Power Turned Off: less than 0.5W 10 - 32.5°C (50 - 90.5°F), Humidity: 20 - 80% RH RoHS and ENERGY STAR			
READING SPEED¹			Simplex	Duplex
DR-2010C	B & W / Grayscale Colour	200/300dpi 200dpi 300dpi	20ppm 20ppm 13ppm	40ipm 40ipm 26ipm
DR-2510C	B & W / Grayscale Colour	200/300dpi 200dpi 300dpi	25ppm 25ppm 15ppm	50ipm 50ipm 30ipm
DOCUMENT SIZE Size Thickness International Standard Card Long Document Mode Paper separation Feeder Capacity Output Resolution Output Mode Binary Grayscale Colour	Width 50-216mm Length 53.9-356mm Automatic Feeding 52-128g/m ² (0.06-0.15mm) Bypass Mode 40-157g/m ² (0.05-0.20mm) Width: 53.9mm, Length: 85.5mm, Thickness: 0.76mm Embossed card and Horizontal scanning is supported 1000mm max. (Adjustable in window control panel) Retard Roller 50 sheets (80g/m ²) 100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi B&W / Error Diffusion / Advanced Text Enhancement I & II 8bit (256 level) Grayscale 24bit color			

PRODUCT FEATURES Image Processing Device	Advanced Text Enhancement (I & II) Prevent Bleed Through / Remove Background Auto Page Size Detection & Deskew Moire Reduction Skip Blank Page Auto Colour Detection Text Orientation Recognition Colour Dropout & Enhancement Auto Power ON/OFF (via USB) Rapid Recovery System Double Feed Detection (Length) Ultrasonic Double Feed detection (DR-2510C only) A3 Folio Mode Scanning Job / User Registration Buttons Batch Separation
BUNDLED SOFTWARE	ISIS / TWAIN Drivers (Windows 2000/XP Pro/ XP Home/Vista) Capture Perfect 3.0 Adobe Acrobat 8 Standard Scansoft Paperport SE Nuance OmniPage SE Presto! Bizcard Reader 5 SE
Options / Consumables Daily Duty Cycle	Exchange Roller Kit Approx. 1,500 scans / day
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change.™ and ®. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. ¹ Speed Specifications are based on scanning A4 Page in portrait orientation. The scanning speed depends on the specification of PC and the setting of functions.	



Partner Programme



imageFORMULA

you can
Canon

Canon Electronics Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

Canon (UK) Ltd
Woodhatch, Reigate
Surrey RH2 8BF
Telephone No: 01737 220000
Facsimile No: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road, Sandyford Industrial Estate
Dublin 18, Ireland
Telephone No: 01-2052400
Facsimile No: 01-2958141
www.canon.ie